

► BB310

# PP


### Block copolymer for sheet application

### Description

**BB310** is a propylene-ethylene block copolymer designed for sheet application. Clear & Soft characteristics of BB310 lead excellent impact strength/transparency balance.

#### Characteristics

► High impact strength



<BB310>

► Low fish-eye level



<General Random PP>

• Optical property (500 µm calendering sheet)

	Method (ASTM)	Unit	BB310
Haze	D1003	%	30

\* Processing temperature :  $230 \,^{\circ}\text{C}$ , \* Chill-roll temperature :  $70 \,^{\circ}{\rm C}$ 

Data performed by or on behalf of Hanwha Total www.cn-plas.com

## **Applications**

- Transparent/Semi-transparent Sheet
- Household Case
- ► Stationery

#### **Physical Properties**

<b>Typical Properties</b>	Method (ASTM)	Unit	BB310
Melt flow index	D1238	g/10min	5.0
Density	D1505	g/cm <sup>3</sup>	0.91
Tensile strength at yield	D638	kg/cm <sup>2</sup>	275
Elongation at break	D638	%	>600
Flexural modulus	D790	kg/cm <sup>2</sup>	10,000
Izod impact strength 23 ℃	D256	kgcm/cm	15
Rockwell hardness	D785	R-scale	63
Heat distortion temp.	D648	C	103

Hanwha 🚺 🚺 Total

\* Data shown above are representative values for reference purposes only, and not to be construed as specifications.

### Food Contact Application

► To apply Hanwha Total BB310 to the food packaging, the verification on the suitability is necessary. In case you might need additional regulatory information, please contact Hanwha Total Polymer Technical Service Team.

#### **Contacts**

#### Product Information & Technical Services <u>www.cn-plas.com</u>

#### **Disclaimer**

This <u>www.cn-plas.com</u> document is copyright of Hanwha Total petrochemicals Co., Ltd. Any and all information and the values in this document are typical properties for reference, not to be confused with, or regarded as specification. Customers are responsible for determining whether our products and information are suitable for their particular purpose and for ensuring that Customer's location and handling practices are in compliance with laws and regulations. HANWHA TOTAL assumes no obligation or liability for the information in this document. NO EXPRESS WARRANTIES ARE

GIVEN EXCEPT FOR ANY APPLICABLE WRITTEN WARRANTIES SPECIFICALLY PROVIDED BY HANWHA TOTAL. ALL IMPLIED WARRANTIES INCLUDING THOSE OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED. HANWHA TOTAL is entitled to alter, change or modify any of the content herein at any time without prior notice, but not under any duty to do so.

\* Data performed by or on behalf of Hanwha Total

LTE21416 2 / 2